

Electrolux Professional Line 5000

Electrolux 100 G-force Washers N-Series, Normal Spin for OPL

Electrolux washers feature Compass Pro, low water consumption, and robust design.

Electrolux Professional 100 G-Force extraction normal spin washers combine world-class reliability with innovative features and programmability.

Electrolux washers increase your productivity, lower utility costs, and provide significant electrical and gas savings. With innovative design and high performance features, Electrolux washers come standard with Compass Pro for easy customization and flexibility.

- Low water consumption
- Single phase 220 volt electrical service reduces installation costs
- Convenient 4-compartment supply dispenser lets you conveniently add all laundry supplies before starting the wash
- Provisions to connect up to 5 liquid supplies
- USB in front for easy access and programming
- Door unlocks immediately at the end of final cycle. No delays.
- Heavy-duty construction with robust steel door and lock, hinges wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Inverter driven motor for smooth and quiet operation, high efficiency
- External liquid manifold improves reliability, workflow, and operation. Best design in the industry. Chemicals are diluted in water reservoir. Reduces maintenance

Compass Pro microprocessor features and benefits

Compass Pro microprocessor provides the ultimate in flexibility and control over your laundry operations.

- Up to 55 programs, 15 custom
- Large display and one control knob for easy program selection
- Two languages displayed simultaneously
- Smart Start real-time clock for delayed start
- Detailed user statistics and programmability
- · Reduce operator error by displaying only the programs you use



Available in 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.





Designed by experts. Inspired by you.

For more information, please visit www.laundrylux.com

Electrolux "N" Models, Normal Spin 100G Washers	W5130N		W5180N		W5250N		W5330N	
Capacity (lb/kg)	30	14	45	20	62	28	77	35
Width (in/mm)	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	31	787	36	914	40 1/2	1029	44	1114
Height (in/mm)	47 7/8	1216	52 15/16	1345	56 1/8	1426	57 11/16	1465
Crated width - (in/mm)	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Height to bottom of door (in/mm)	16 11/16	424	19 11/16	500	20 15/16	532	22 3/8	568
Door opening diameter (in/mm)	14 3/8	365	15 9/16	395	17 2/16	435	17 1/8	435
Cylinder volume (ft3/l)	4.6	130	6.4	180	8.8	250	11.7	330
Cylinder diameter (in/mm)	23 7/16	595	25 9/16	650	28 9/16	725	31 5/16	795
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/8	104	3 15/16	100	4 1/8	104
leight to electrical connection (in/mm)	36 1/4	920	41 5/16	1049	44 7/16	1129	46	1168
Height to water connections (in/mm) (approx)	43 11/16	1109	48 11/16	1237	51 1/2	1308	53 1/16	1347
Dynamic load (lb/kN)	540+/-697	2.4+/-3.1	652+/-877	2.9+/-4.7	854+/-1102	3.8+/-4.9	1034+/-1259	4.6+/-5.
Dynamic frequency (Hz)	9.1		8.8		8.3		7.9	
Noise level (dBA)	69		72		71		74	
Crated weight (lb/kg)	370	168	492	223	615	279	717	325
Operating Speeds								
Vash (rpm)	46		44		42		40	
Extract (rpm/G-Force)	548/100		525/100		497/100		474 / 100	
Electrical Requirements (standard)								
/oltage/frequency/phase	208-240/60/1		208-240/60/1		208-240/60/1		208-240/60/1	
Full-load current (Amps) / Ckt breaker (Amps)	4.2 / 15		6.3 / 15		5.3 / 15		6.7 / 15	
/oltage/frequency/phase	120/60/1		120/60/1		120/60/1		-	
ull-load current (Amps) / Ckt breaker (Amps)	8.3 / 15		10.8 / 15		9.2 / 20		-	
Nater Information								
nlet fittings (* = 3 inlets)	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
low (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

Electrolux Professional Line 5000 The all-in-one business solution for your on-premises laundry.



Smart Dosing provides unmatched efficiency and economy

- System automatically calculates correct amount of detergent
- More efficient, better results
- Cuts chemical costs



External liquid chemical manifold - Best design in the industry

- Chemicals are diluted in water
 reservoir
- Improves reliability, operation, workflow
- Reduces maintenance



Cost savings in water and energy with Automatic Water Savings (AWS)

(EII

- Determines load weight and adds precisely
 the correct amount of water
- Up to 30% water savings automatically
- Less water to heat
- Reduces water and energy consumption



Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

Laundrylux 800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338 516-371-4400 • F 516-371-4204 • sales@laundrylux.com Parts: 516-371-2000 • F 516-371-4029 • parts@laundrylux.com Tech Support: 516-371-0700 • F 516-371-4029 • service@laundrylux.com En Mexico: Llame gratis a este numero 001-800-010-1010

