ON-PREMISES SOFTMOUNT WASHER EXTRACTOR





9YN40



▲ ④ ▷ ⊗ ● 1 2 3 ● □ □ □ 0 1 2 3 ● □ □ □ □ □ □ □ □ □ ● □

FEATURES

- Freestanding, high spin, 400 G-Force
- Stainless steel top, front, and side panels
- Stainless steel cylinder and tub
- Patented Cascade [™] cylinder for better washability
- XControl+ fully programmable control
- Patented soap hopper
- High water inlets
- Large drain valve
 - Front access to vital parts for easy
- maintenance
- USB plug on the back panel and control board
- Warranty: First three years on all parts;
- First five years frame and cylinder shaft assembly; First five years on cylinder bearings and bearing seals (parts only)

OPTIONS

- Third water inlet
- Steam heating





MODEL	PYN40
CONTROL OPTION	XControl+
CAPACITY - lb (kg)	40 (18)
OVERALL WIDTH - in (mm)	38.18 (970)
OVERALL DEPTH - in (mm)	38.18 (970)
OVERALL HEIGHT - in (mm)	55.51 (1410)
CYLINDER DIAMETER - in (mm)	29.53 (750)
CYLINDER DEPTH - in (mm)	16.14 (410)
CYLINDER VOLUME - cu. ft (liters)	6.4 (180)
DOOR OPENING SIZE - in (mm)	18.11 (460)
DOOR BOTTOM TO FLOOR - in (mm)	18.77 (477)
WASH SPEED - RPM	42
EXTRACT SPEED - RPM	980
EXTRACT G-FORCE	400
WATER INLET CONNECTION - in (mm)	2 x 0.75 (19)
STEAM INLET CONNECTION - in (mm)	0.5 (13)
DRAIN CONNECTION - in (mm)	3 (76)
FLOOR TO DRAIN OUTLET CENTER - in (mm)	5.21 (132)
SIDE TO DRAIN OUTLET CENTER - in (mm)	10.62 (270)
MOTOR POWER CONSUMPTION - hp (kw)	2.95 (2.20)
VOLTAGE/CIRCUIT BREAKER - FLA 208-240	0/60/1 20-14.2
440-480	0/60/3 –
SHIPPING DIMENSIONS APPROX in (mm)	Width 40.35 (1025)
	Depth 39.96 (1015)
	Height 61.02 (1550)
NET WEIGHT - Ib (kg)	838 (380)
SHIPPING WEIGHT - Ib (kg)	871 (395)
AGENCY APPROVALS	cCSAus

DIM	ENSIONS	PYN40
Α.	OVERALL WIDTH - in (mm)	38.18 (970)
В.	OVERALL DEPTH - in (mm)	38.18 (970)
C.	OVERALL HEIGHT - in (mm)	55.51 (1410)
D.	DOOR BOTTOM TO FLOOR - in (mm)	18.77 (477)



