





### GYRO BALANCING SYSTEM

3-D Gyro System keeps loads in balance so they are completed in less than 29min. Our Gyro Balancing System provides optimized performance by using an advanced algorithm that allows for errorless spinning and on time cycle completion.



## INVERTER DIRECT DRIVE™ MOTOR

Our Inverter Direct Drive™ Motor has no belts, which cuts down on maintenance calls and extends the life of the product.



#### **TURBOWASH 3D**

TurboWash expedites the cleaning process to maximize profits. Turbo Wash 3D gets clothes cleaner faster and saves money on your utility bills



### FRONT SERVICE PANEL


We know servicing and maintaining your fleet takes time and money, so we added a removable Front Service Panel that lets you get inside the washers quickly without having to uninstall them. Pump is located in front for easier access.



#### **TOP LOAD WASHER SPECIFICATIONS**

MODEL		CTD2=FC+D+
MODEL		CTD27TS*R*
CYLINDER	C: /n\	265 (102.4)
Drum Volume	cu.ft (f)	3.65 (103.4)
Diameter	in. (mm)	21.6 (548)
Depth	in. (mm)	15.4 (391.8)
DIMENSIONS		
Product (WxHxD)	in	27 x 28.4 x 41.1
	mm	686 x 721 x 1045
Carton (WxHxD)	in	29.1 x 30.9 x 43.7
	mm	740 x 785 x 1110
Weight (Product/Carton)	lb	121/134
	kg	55/61
SPEED		
Wash	RPM	Motor: 0~532, Pulsator: 0~140
Extract (High Speed)	RPM	720
RATING <sup>0</sup>		
Electric Ratings	V/Hz/A	120/60/3
*CONSUMPTION INDEX <sup>0</sup>		
Water	gal (f)	DOE Max 25.1 (95)
Electricity	kW	100~120V/0.2
NOISE & CYCLE TIME		
Noise Level (Sound Power)	dB	Lower than 60
Program Duration in Minutes (Default) <sup>0)</sup>	min	29
SYSTEM & CONTROL		
Inverter Direct Drive Motor		0
Drain System		BLDC Pump Drain
Gyro Sensor		0
Damper		4 Horizontal Friction Dampers
PROGRAMS <sup>0</sup>		
		Hot
Program List		Warm
		Cold
		Normal ECO Delicates (Long Key) <sup>5</sup>
		Add Deep Rinse / Custom PGM (OPL) (Long Key) <sup>5</sup>
EXTERNAL FINISH		And Deep Milise / Caswill Fairi (OFL) (Living Ney)
		Stainless Steel
Drum  CIRCUIT PROTECTION		Stail liess Steet
		0/250/4
PCB Fuse - Main Control Board	amps	8 (250V)

8 (250V)



Side

# 33 9/16" inch 30"inch 3 1/2" inch inch 28 7/16" — inch

#### **PRODUCT** IMAGE

PCB Fuse - Filter Assembly



Coin Convertible

Card Type

amps

